

FIAMM

Industrial Batteries

HIGHLITE FLX series



12FLX400

FIAMM's FLX batteries have been specifically designed to achieve optimal performance in:

- + High-Rate UPS Systems
- + Emergency Power Applications

A compact footprint provides easy installation in cabinets and racks with minimal space clearance.

Capable of protecting the critical load from power disturbances.

Standby Products

Product Features

- + High integrity design with superior energy density in industry standard footprint
- + Microporous absorbent glass mat "AGM" technology, low maintenance, 99% recombination, non-spillable
- + 10 year design life @ 25°C
- + UL94V-0 rated flame retardent plastic
- + Gravity cast, high purity, Lead-Tin Calcium grids for low corrosion and high rate performance
- + Individual cell flame arrestors
- + Non-spillable, unrestricted for air/water/surface transport
- + Handles, integrated design, flush mount

Technical Data


BATTERY TYPE	NOMINAL VOLTAGE (V)	CAPACITY at 77°F Watt per Cell 15 mins 1.67V/C	CAPACITY at 77°F (AH) 8 hours 1.75V/C	DIMENSIONS in.			WEIGHT lbs/(kg)	TERMINALS
				Top Length/ Bottom Length	Top Width/ Bottom Width	Top Height/ Bottom Height		
12 FLX 400	12	415	88.0	13.31/12.74	6.85/6.57	8.46	73.3/(33.3)	1/4" - 20

Applicable Standards

Telcordia (Bellcore) SR-4228
 Telcordia (Bellcore) TR-NWT-001200
 Telcordia (Bellcore) TR-NWT-000909
 UL Recognized
 UL 94 Class V-0
 UL 1778
 IEC 60896 Part 21-22

Terminal Type

Torque: 106 in.lbs.



FLX400 DISCHARGE WATTS PER CELL AT 77°F

Volts per Cell	MINUTES						
	30	60	120	180	240	300	480
1.60	237	132	69.2	49.1	38.4	32.1	21.8
1.65	233	131	68.9	48.8	38.2	32.0	21.7
1.67	250	142	68.8	48.7	38.1	31.9	21.7
1.70	229	129	68.6	48.5	38.0	31.9	21.7
1.75	219	125	68.3	48.2	37.8	31.7	21.5

FLX400 DISCHARGE AMPERES AT 77°F

BATTERY TYPE	MINUTES						
	30	60	120	180	240	300	480
1.60	129	71.2	36.8	26.0	20.2	16.9	11.4
1.65	125	69.5	36.3	25.6	20.0	16.7	11.3
1.67	123	68.5	36.0	25.4	19.9	16.6	11.3
1.70	122	67.9	35.9	25.3	19.8	16.5	11.2
1.75	115	65.2	35.3	24.8	19.4	16.3	11.0

Electrical Characteristics

- ✦ FLOAT VOLTAGE CHARGE AT 77°F: 13.62 V/block (13.6 - 13.8)
- ✦ FLOAT VOLTAGE COMPENSATION WITH TEMPERATURE: -8.3 mV/°F per block
- ✦ SELF-DISCHARGE AT 77°F: < 2% / month

